

LG Commercial Sheet Vinyl

Maintenance and Cleaning Guide

GENERAL ADVICE

- Clean the floorcovering regularly.
- Always follow dosage instructions carefully. Resilient floors are damaged by solvents.
- Wipe up any grease and spilt oil immediately, as they may damage the surface.
- Legs on furniture, along with any angular edges or heavy weights should be placed on smooth protective pads to avoid damage to the flooring.

INITIAL TREATMENT – Homogeneous Commercial Sheet Vinyl

- Please ensure all joints are hot welded, fully cure and all traces of adhesive is removed prior to carrying out any wet cleaning. Clean floor area with a soft broom or preferably a dust control mop.

PREVENTIVE CARE

Most dirt comes from outdoors. Installing well suited doormats at the entranceways will prevent 80% of the potential dirt and moisture from entering the premises. To remain effective, doormats should be vacuumed daily.

DAILY AND REGULAR CLEANING

- Dry mopping: Remove dust and dirt with yarn or microfibre mops, or disposable mops, dry or impregnated. You can also use a suitable broom with soft bristles.
- Vacuum cleaning: Vacuum your flooring regularly to keep dust to a minimum.
- Damp mopping: Use a mop dampened with water or detergent solution. It is essential that water does not stay on the floor or leave a film.
- Combined machine (for large areas): Use diluted neutral detergent as per the manufacturer's instructions.
- Spray cleaning (spray cleaning and buffing in one operation): mix water, neutral detergent and polymer in the container tank.
- Stains and spills should be cleaned up as quickly as possible, when they are still fresh, and then rinsed with clean water.

PERIODIC CLEANING

Light soiling Spray buffing: Spray clean with neutral detergent and floor maintainer.

Heavy soiling Machine scrubbing and wet vacuuming:

- Apply a cleaning solution as per the manufacturer's instructions and guides.
- Clean the floor using a heavy-duty single disc scrubbing machine.
- Vacuum up the dirty water immediately. Rinse with clean water and allow the floor to dry.

If needed, dry buffing: When necessary, dry buff to restore the surface gloss.